



DUN Signature

Premium Touring Ride With A Performance Attitude



Dry Traction	Wet Traction	Snow Traction	Ride Comfort	Quiet Ride
7	7	8	8	8
Features			Benefits	
<ul style="list-style-type: none"> ° T rated 75,000 miles or H/V rated 60,000 miles Tread Life Limited Mileage Warranty ° VersaLoad Technology™ ° Elliptical Beads and Constant Gauge Chafer ° Jointless Band Technology™ (Available only on H- and V-speed rated sizes.) ° Stability Rib ° Highly detailed tread pattern including Multi-Pitch Tread Design Technology™ and Evaqua Grooves™ ° Dimensionally Stable Polyester™ 			<ul style="list-style-type: none"> ° Confidence in your purchase decision ° Consistent handling, ride comfort and tread wear in a wide range of load conditions ° Help provide a tighter tire/wheel fit for superb handling and ride comfort ° Helps maintain the tire's structural integrity and enables smooth performance at highway speeds ° Stays in constant contact with the road for consistent steering response and driving feedback ° Helps deliver responsive dry handling, effective water evacuation, even wear, noise reduction and confident all-season capability ° Helps maintain tire uniformity for a smooth, comfortable ride 	

Tire Dimension Data & Other Technical Information

Tire Size	Product Code	Material	Srvc Desc	Side wall	App Rim Width (min)	App Rim Width (max)	Meas Rim Width	Overall Width	Overall Diam.	Max Load	RPM	Tread Depth (32nds)	Weight (lbs)	Limited Wmty Miles KM	U.T.Q.G.
P175/65R14	26600206500198526	81T	BSW	5.0	6.0	5.00	7.0	23.0	1019	909	11	16.7	75000 120000	700 A B	
P185/65R14	26600206600198527	85T	BSW	5.0	6.5	5.50	7.5	23.5	1124	891	11	18.5	75000 120000	700 A B	
P195/55R15	26600225600201697	84V	BSW	5.5	7.0	6.00	7.9	23.4	1102	892	11	20.7	60000 95000	500 A A	
P185/60R15	26600206000198528	84T	BSW	5.0	6.5	5.50	7.5	23.8	1102	880	11	17.6	75000 120000	620 A B	
195/60R15	26600207400202974	88T	BSW	5.5	7.0	6.00	7.9	24.2	1235	863	11	19.3	75000 120000	700 A B	
195/60R15	26600216900202979	88H	BSW	5.5	7.0	6.00	0.0	0.0	1235	863	11	19.9	60000 95000	500 A A	
P205/60R15	26600216100198565	90H	BSW	5.5	7.5	6.00	8.2	24.7	1301	846	11	20.6	60000 95000	500 A A	
P215/60R15	26600206200198533	93T	BSW	6.0	7.5	6.50	8.7	25.2	1411	831	11	23.2	75000 120000	700 A B	
P215/60R15	26600216200198567	93H	BSW	6.0	7.5	6.50	8.7	25.2	1411	831	11	22.6	60000 95000	500 A A	
185/65R15	26600216800202978	88H	BSW	0.0	0.0	0.00	0.0	0.0	1235	855	11	19.8	60000 95000	500 A A	
195/65R15	26600207500202975	91T	BSW	0.0	0.0	0.00	0.0	0.0	1356	0	11	20.0	75000 120000	700 A B	
195/65R15	26600216600198564	91H	BSW	5.5	7.0	6.00	7.9	25.0	1356	836	11	20.6	60000 95000	500 A A	
205/65R15	26600216700198566	94H	BSW	5.5	7.5	6.00	8.3	25.5	1477	821	11	21.8	60000 95000	500 A A	
P205/65R15	26600206800198531	92T	BSW	5.5	7.5	6.00	8.3	25.5	1400	821	11	21.2	75000 120000	700 A B	
P205/70R15	26600207000198532	95T	BSW	5.0	7.0	6.00	8.3	26.4	1499	793	11	22.4	75000 120000	700 A B	
215/70R15	26600207600202976	98T	BSW	0.0	0.0	0.00	0.0	0.0	1653	0	11	24.3	75000 120000	700 A B	
205/50R16	26600217100202982	87H	BSW	0.0	0.0	0.00	0.0	0.0	1201	904	11	21.6	60000 95000	500 A A	
205/55R16	26600207700202977	91T	BSW	0.0	0.0	0.00	0.0	0.0	1356	0	11	22.1	75000 120000	700 A B	
205/55R16	26600215600198675	91H	BSW	5.5	7.5	6.50	8.4	24.9	1356	839	11	21.7	60000 95000	500 A A	
215/55R16	26600217000202980	93H	BSW	0.0	0.0	0.00	0.0	0.0	1433	0	11	23.5	60000 95000	500 A A	
P205/60R16	26600206300198536	91T	BSW	5.5	7.5	6.00	8.2	25.7	1356	815	11	22.1	75000 120000	700 A B	
P205/60R16	26600216400198676	91H	BSW	5.5	7.5	6.00	8.2	25.7	1356	815	11	22.1	60000 95000	500 A A	

P215/60R16	26600206400198538	94T	BSW	6.0	7.5	6.50	8.7	26.2	1477	799	11	23.8	75000 120000	700 A B
P215/60R16	26600226000198569	94V	BSW	6.0	7.5	6.50	8.7	26.2	1477	799	11	25.4	60000 95000	500 A A
225/60R16	26600207300198540	98T	BSW	6.0	8.0	6.50	9.0	26.6	1653	786	11	25.1	75000 120000	700 A B
225/60R16	26600216300198570	98H	BSW	6.0	8.0	6.50	9.0	26.6	1653	786	11	25.3	60000 95000	500 A A
P235/60R16	26600205900201275	99T	BSW	6.5	8.5	7.00	9.5	27.1	1709	772	11	27.1	75000 120000	700 A B
P205/65R16	26600206900198537	94T	BSW	5.5	7.5	6.00	8.2	26.5	1477	790	11	25.7	75000 120000	700 A B
215/65R16	26600207200198539	98T	BSW	6.0	7.5	6.50	8.7	27.0	1653	774	11	24.9	75000 120000	700 A B
235/65R16	26600215300203677	103T	BSW	0.0	0.0	0.00	0.0	0.0	1929	0	11	26.6	0 0	700 A B
P215/50R17	26600225000201699	93V	BSW	6.0	7.5	7.00	8.9	25.5	1433	819	11	26.1	60000 95000	500 A A
225/50R17	26600215400203678	94V	BSW	0.0	0.0	0.00	0.0	0.0	1477	807	11	26.7	60000 95000	500 A A
225/55R17	26600225700202981	97V	BSW	0.0	0.0	0.00	0.0	0.0	1609	0	11	27.0	60000 95000	500 A A
P225/55R17	26600205600198561	95T	BSW	6.0	8.0	7.00	9.2	26.8	1521	780	11	26.1	75000 120000	700 A B
235/55R17	26600215800208075	99H	VSB	0.0	0.0	0.00	0.0	0.0	1709	0	11	26.7	0 0	500 A A
215/60R17	26600215900208076	96H	VSB	0.0	0.0	0.00	0.0	0.0	1565	0	11	25.2	0 0	500 A A
P225/60R17	26600205800201276	98T	BSW	6.0	8.0	6.50	9.0	27.6	1653	756	11	28.6	75000 120000	700 A B
P215/65R17	26600215200203676	98T	BSW	0.0	0.0	0.00	0.0	0.0	1653	0	11	24.9	75000 120000	700 A B