



## DUN SP 60

Confident All-Season Traction



Dry Traction	Wet Traction	Snow Traction	Ride Comfort	Quiet Ride
7	7	8	8	7
Features			Benefits	
<ul style="list-style-type: none"> <li>◦ Traction Web Technology™</li> <li>◦ Dimensionally Stable Polyester™</li> <li>◦ Biting edges created by MSI Traction Technology™</li> <li>◦ Lateral Tread Grooves</li> <li>◦ Multiple Tread Block Edges</li> <li>◦ Cross Sipes</li> <li>◦ Three wide water-siphoning circumferential grooves</li> <li>◦ Multi-Pitch Tread Design Technology™</li> <li>◦ Wide, high-density steel belts</li> <li>◦ Hard rubber bead apex and clinch package</li> <li>◦ Serrated black sidewall or classic white sidewall</li> </ul>			<ul style="list-style-type: none"> <li>◦ Enhances traction and steering for responsive wet, dry and</li> <li>◦ situational handling</li> <li>◦ Helps maintain tire uniformity for a smooth, comfortable ride</li> <li>◦ Optimize all-season traction for excellent control without</li> <li>◦ compromising long mileage</li> <li>◦ Helps maximize water evacuation for confident wet road handling</li> <li>◦ Helps reduce noise for a quiet ride</li> <li>◦ Confident cornering control and long, even tread wear</li> <li>◦ Precise, responsive handling</li> <li>◦ Complement any vehicle's appearance</li> </ul>	

### Tire Dimension Data & Other Technical Information

Tire Size	Product Code	Material Number	Svc Desc	Side wall	App Rim Width (min)	App Rim Width (max)	Meas Rim Width	Overall Width	Overall Diam.	Max Load	RPM	Tread Depth (32nds)	Weight (lbs)	Limited Wrmty Miles KM	U.T.Q.G.
P175/65R14	26300683500188427	81S	BSW	5.0	6.0	5.00	7.0	23.0	1019	913	9	15.3	65000 105000	600 A B	
P185/65R14	26300683600188429	85S	BSW	5.0	6.5	5.50	7.4	23.5	1124	894	9	16.1	65000 105000	600 A B	
P195/65R14	26300687100188195	88S	BSW	5.5	7.0	6.00	7.9	24.0	1235	875	9	17.5	65000 105000	600 A B	
P175/70R14	26300684300188194	84S	BSW	4.5	6.0	5.00	7.0	23.7	1102	889	9	15.4	65000 105000	600 A B	
P185/70R14	26300684000188191	87S	BSW	4.5	6.0	5.50	7.4	24.3	1201	870	9	17.3	65000 105000	600 A B	
P195/70R14	26300687700188430	90S	BSW	5.0	6.5	6.00	7.9	24.8	1312	852	10	18.1	65000 105000	600 A B	
P205/70R14	26300599000188161	93S	WSW	5.0	7.0	6.00	8.2	25.4	1433	835	10	20.8	65000 105000	600 A B	
P185/75R14	26300593900187784	89S	WSW	4.5	6.0	5.00	7.2	25.0	1290	848	11	17.9	65000 105000	600 A B	
P195/75R14	26300598100187786	92S	WSW	5.0	6.5	5.50	7.7	25.5	1400	829	11	19.1	65000 105000	600 A B	
P205/75R14	26300597500187790	95S	WSW	5.0	7.0	5.50	8.0	26.1	1532	812	11	21.4	65000 105000	600 A B	
P195/65R15	26300684500188192	89S	BSW	5.5	7.0	6.00	7.9	25.0	1279	839	9	18.6	65000 105000	600 A B	
P205/65R15	26300685000188431	92S	BSW	5.5	7.5	6.00	8.2	25.5	1400	823	11	19.5	65000 105000	600 A B	
P215/65R15	26300685500189465	95S	BSW	6.0	7.5	6.50	8.7	26.0	1510	808	10	20.9	65000 105000	600 A B	
P205/70R15	26300597800187789	95S	WSW	5.0	7.0	6.00	8.2	26.3	1499	801	10	21.3	65000 105000	600 A B	
P215/70R15	26300599200187792	97S	WSW	5.5	7.0	6.50	8.7	26.9	1620	786	10	24.6	65000 105000	600 A B	
P225/70R15	26300596600188172	100S	WSW	6.0	7.5	6.50	9.0	27.4	1753	771	10	26.5	65000 105000	600 A B	
P205/75R15	26300598200187791	97S	WSW	5.0	7.0	5.50	8.0	27.1	1598	780	11	22.2	65000 105000	600 A B	
P215/75R15	26300599300187793	100S	WSW	5.5	7.0	6.00	8.5	27.7	1742	765	11	26.7	65000 105000	600 A B	
P205/55R16	26300684900189466	89S	BSW	5.5	7.5	6.50	8.4	24.9	1279	836	11	21.2	65000 105000	600 A B	
P215/60R16	26300686000188193	94S	BSW	6.0	7.5	6.50	8.7	26.1	1477	799	10	22.1	65000 105000	600 A B	

P225/60R16	26300686500188433	97S	BSW	6.0	8.0	6.50	9.0	26.6	1609	785	11	23.5	65000 105000	600 A B
215/65R16	26300686100189467	98S	BSW	6.0	7.5	6.50	8.7	27.0	1653	776	11	24.1	65000 105000	600 A B