

# KELLY TIRES™

## Explorer® Plus

Versatile All-Season Performance

- 1 Isolated tread elements, full slotting and blading
- 2 Two steel belts
- 3 Distinctive outlined black serrated lettering
- 4 Polyester radial cord body
- 5 Tread Life Limited Warranty\* (P-Metric sizes only)



\* See Tread Life Limited Warranty Brochure for complete details

### ▼ Kelly Tires Features Sizes And Specs

TIRE SIZE	SERVICE DESCR.	LOAD RANGE	SIDE-WALL DESCR.	APPROVED RIM WIDTH (INS)	MEAS. RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	TREAD DEPTH (IN 32NDS)	MAX LOAD (LBS)
185/60R15	118T	SL	SBL	0.0 - 0.0	0.00	185	0.0	10/32	1,102@44
185/65R15	118T	SL	SBL	0.0 - 0.0	0.00	185	0.0	10/32	1,235@44
195/60R15	118T	SL	SBL	0.0 - 0.0	0.00	195	0.0	10/32	1,235@44
205/55R16	118T	SL	SBL	5.5 - 7.5	6.50	205	24.9	10/32	1,356@44
205/60R15	118T	SL	SBL	0.0 - 0.0	0.00	205	0.0	10/32	1,356@44
215/65R15	118T	SL	SBL	6.0 - 7.5	6.50	215	26.0	10/32	1,565@44
215/65R16	118T	SL	SBL	6.0 - 7.5	6.50	215	27.0	10/32	1,653@44
225/60R16	118T	SL	SBL	6.0 - 8.0	6.50	225	26.6	10/32	1,653@44
P175/65R14	112S	SL	VSB	5.0 - 6.0	5.00	175	23.0	10/32	1,019@44
P175/70R13	112S	SL	VSB	4.5 - 6.0	5.00	175	22.7	10/32	1,036@44
P185/65R14	112S	SL	VSB	5.0 - 6.5	5.50	185	23.5	10/32	1,124@44
P185/70R14	112S	SL	VSB	4.5 - 6.0	5.50	185	24.3	10/32	1,201@44
P185/75R14	112S	SL	VSB	4.5 - 6.0	5.00	185	25.0	10/32	1,290@44
P195/65R15	112S	SL	VSB	5.5 - 7.0	6.00	195	25.0	10/32	1,279@44
P195/70R14	112S	SL	SBL	5.0 - 6.5	6.00	195	24.8	10/32	1,312@44
P195/75R14	112S	SL	VSB	0.0 - 0.0	0.00	195	0.0	10/32	1,400@44
P205/65R15	112S	SL	SBL	5.5 - 7.5	6.00	205	25.5	10/32	1,400@44
P205/70R15	112S	SL	VSB	5.0 - 7.0	6.00	205	26.3	10/32	1,499@44
P205/75R14	112S	SL	VSB	5.0 - 7.0	5.50	205	26.1	10/32	1,532@44
P215/60R15	118T	SL	SBL	0.0 - 0.0	0.00	215	0.0	10/32	1,411@44
P215/60R16	118T	SL	SBL	6.0 - 7.5	6.50	215	26.1	10/32	1,477@44
P215/70R15	112S	SL	SBL	5.0 - 7.0	6.50	215	26.9	10/32	1,620@44
P215/75R15	112S	SL	VSB	5.5 - 7.0	6.00	215	27.7	10/32	1,742@44