

# Firestone®

## **FIREHAWK® WIDE OVAL** **WITH UNI-T**

Racing heritage. Retro look. Updated with UNI-T technology. Today's Firehawk Wide Oval is a lot more tire than it once was. Now, performance is ultra high. Turns are tight. Handling is precise. Traction is exceptional in both wet and dry conditions. The Wide Oval has been inspired by the track. This time, it's ready to rule the road.

### **WARRANTY SUMMARY**

**GOLD PLEDGE LIMITED WARRANTY††**  
**BUY & TRY 30 DAY GUARANTEE‡**



††Replacement at no charge (excluding taxes and disposal fees) if your Firestone tire becomes unusable for any reason within the manufacturer's control for up to 3 years from date of purchase or 4 years from date of manufacture, whichever is to the owner's advantage. Certain restrictions and limitations may apply.

‡Original proof of purchase required to take advantage of the 30 Day Test Drive. Tires must be returned within 30 days of purchase. Does not apply to tires supplied as original equipment on new vehicles.





**Silica**

Tread rubber compound reinforced with Silica enhances traction, especially in cold, wet weather when conventional rubber compounds can get brittle and lose grip.

**Innovative Compound- Longer Is Stronger**

L.L. Carbon utilizes a special form of molecular re-engineered carbon black, a key factor in improving tire wear while enhancing wet performance.

**Innovative Tire Design - A Comprehensive Tire Design Method**

This method improves handling in wet or dry conditions and reduces irregular treadwear by combining an ideal tread design, casing shape, materials and construction.

**Spiral Wrap**

Spiral Wrap is a continuous nylon wrap that encircles the whole tire, helping the tire hold its original shape to improve high speed capability.

**Innovative Roundness- Roundness Is Better**

Rounder overall tire shape provides better balance for wet or dry handling.

**Consistent Surface Contact (C.S.C)**

C.S.C., a pattern of tread blocks designed for uniform contact pressure, improves dry and wet handling, reduces irregular wear, and results in better ride comfort.

**Weather Grip HP Tread Compound**

This is a special performance tread compound formulation containing SBR and L.L. Carbon in a blend designed to promote long-wearing durability and outstanding wet performance without sacrificing dry performance.

## Firehawk Wide Oval TIRE SPECIFICATIONS

Size	Service Description	Load Range	Speed Rating	Sidewall Styling	Article Number	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Width	Static Load Radius	Tread Depth (32")	RPM	Tire Weight	UTQG
P225/60R16	97W		W	BW	027498	6.0-8.0	6.5	26.6	8.9	7.3	12.1	10.0	783	27	320 AA A
P205/55R16	89W		W	BW	027549	5.5-7.5	6.5	24.9	8.4	6.6	11.5	10.0	837	23	320 AA A
P225/55R16	94W		W	BW	027600	6.0-8.0	7.0	25.7	9.1	7.2	11.8	10.0	807	26	320 AA A
205/50R16	87W		W	BW	027651	5.5-7.5	6.5	24.1	8.4	6.6	11.1	10.0	864	22	320 AA A
P225/50R16	91W		W	BW	027702	6.0-8.0	7.0	24.8	9.1	7.2	11.5	10.0	837	24	320 AA A
P245/50R16	96W		W	BW	028705	7.0-8.5	7.5	25.6	9.8	7.9	11.8	10.0	811	28	320 AA A
235/50R17	96W		W	BW	027736	6.5-8.5	7.5	26.3	9.6	7.6	12.1	10.0	792	27	320 AA A
215/45R17	87W		W	BW	027770	7.0-8.0	7.0	24.7	8.5	7.5	11.5	10.0	843	23	320 AA A
245/45R17	95W		W	BW	027821	7.5-9.0	8.0	25.7	9.6	8.6	12.0	10.0	798	27	320 AA A
P255/45R17	92W		W	BW	027838	8.0-9.5	8.5	26.1	10.1	8.9	12.0	10.0	798	28	320 AA A
205/40R17 XL	84W		W	BW	070933	7.0-8.0	7.5	23.5	8.5	7.0	11.0	10.0	886	20	320 AA A
265/40R17	96W		W	BW	027923	9.0-10.0	9.5	25.4	10.8	9.1	11.7	10.0	823	27	320 AA A
P275/40R17	98W		W	BW	027940	9.0-11.0	9.5	25.7	11.0	9.5	11.9	10.0	811	28	320 AA A
P285/40R17	100W		W	BW	027974	9.5-11.0	10.0	26.0	11.5	9.9	11.9	10.0	811	30	320 AA A
225/40R18	88W		W	BW	027991	7.5-9.0	8.0	25.1	9.1	7.8	11.8	10.0	830	24	320 AA A
295/35R18	99W		W	BW	028025	10.0-12.0	10.0	26.1	11.9	10.1	12.2	10.0	792	32	320 AA A
* P245/40R18	88Y		Y	BW	057333	8.0-9.5	8.5	25.7	9.6	8.2	12.0	10.0	811	30	320 AA A
P255/45R19	100H		H	BW	057384	8.0-9.5	8.5	28.0	10.1	8.9	13.0	10.0	757	31	320 AA A
* P285/35R19	90Y		Y	BW	057367	9.5-11.0	10.0	26.7	12.5	8.0	12.5	10.0	793	39	320 AA A
245/40R20	99W XL		W	BW	087763	8.0-9.5	8.5	27.7	9.8	8.5	13.0	10.0	752	29	320 AA A
275/35R20	98W		W	BW	053168	9.0-11.0	9.5	27.6	11.1	9.5	12.9	10.0	755	31	320 AA A
P295/40R20	106H		H	BW	057418	10.0-12.0	10.0	29.3	11.7	10.2	13.6	10.0	725	33	320 AA A

\* RFT SIZE

