

## High Performance Radial

- Jointless spiral-wrapped full nylon cap for added strength and stability
- Double steel-belted construction for long-lasting wear and uniformity
- Ultra-stiff bead filter and solid center rib provide excellent cornering, acceleration and handling
- Aggressive tread design delivers excellent water dispersion and all-season performance
- Directional tread pattern
- Specially formulated compound to provide superior traction
- M&S rated
- *UTQG: Treadwear 300; Traction A; Temp. A (V and W Rated)*



# MA-V1

Size	Sidewall	Rim	Tread Depth	Section Width	Tire Diameter	Max Load/ PSI Single	Stock Number	List Price
<b>195/50R15 82V</b>	BLK	6.0	9/32	7.7	22.8	1047/44	TP00045100	
<b>205/50R15 86V</b>	BLK	6.5	11/32	8.4	23.1	1168/44	TP00046100	
<b>195/50R16 84V</b>	BLK	6.0	9/32	7.7	23.8	1074/44	TP00047100	
<b>225/50R16 92V</b>	BLK	7.0	10/32	9.2	25.0	1389/44	TP00048100	
<b>205/45R16 83V</b>	BLK	7.0	9/32	8.1	23.2	1074/44	TP39585000	
<b>225/45R16 89V</b>	BLK	7.5	10/32	8.7	23.9	1279/44	TP39590000	
<b>205/45R17 84V</b>	BLK	7.0	9/32	8.0	24.3	1102/44	TP39586200	
<b>235/45R17 93V</b>	BLK	8.0	10/32	9.3	26.3	1433/44	TP42004000	
<b>255/45R18 99V</b>	BLK	8.5	10/32	10.1	27.1	1709/44	TP43520000	
<b>205/40R16 79V</b>	BLK	7.5	9/32	8.3	22.4	963/44	TP39580200	
<b>215/40R16 82V</b>	BLK	7.5	10/32	8.4	22.8	1047/44	TP39581200	
<b>215/40R17 83V</b>	BLK	7.5	10/32	8.4	23.9	1073/44	TP42504200	
<b>235/40R17 90V</b>	BLK	8.5	10/32	9.5	24.4	1323/44	TP39582000	
<b>255/40R17 94V</b>	BLK	9.0	10/32	10.2	25.0	1477/44	TP42500200	
<b>275/40R17 98V</b>	BLK	9.5	10/32	10.9	25.7	1653/44	TP42508200	
<b>225/40R18 88V</b>	BLK	8.0	10/32	9.1	25.0	1235/44	TP43100200	
<b>235/40R18 91V</b>	BLK	8.5	10/32	9.4	25.5	1356/44	TP43102200	
<b>255/35ZR18 90W</b>	BLK	9.0	9/32	10.2	25.0	1323/44	TP00050100	
<b>265/35ZR18 93W</b>	BLK	9.5	10/32	10.7	25.3	1433/44	TP00051100	

ALWAYS OBEY POSTED SPEED LIMITS AND ADJUST YOUR DRIVING TO THE EXISTING ROAD CONDITIONS  
 PLEASE NOTE: Tire spec data is subject to change  
 WARNING – NEVER ATTEMPT TO MOUNT A 16" TIRE ON A 16.5" RIMI!