

## TIMBERLINE AT COMMERCIAL



Outline	LR	LI/SR	#	Design	Optional	Section	Overall	Tread	Tread	Static	Revs		
White Letter			Article #	FET	Rim Width	Rim Width	Width	Dia.	Width	Depth (32nds)	Loaded Radius	Per Mile	Wt.
LT265/75R16	E	123/120 R	204-916	_____	7.5	7.0 - 8.0	10.5	31.9	8.0	18	14.8	654	46
LT265/70R17	E	121/118 R	204-321	_____	8.0	7.0 - 8.5	10.7	31.9	8.6	17	14.2	659	47
<b>Black</b>													
LT215/85R16	E	115/112 R	204-015	_____	6.0	5.5 - 7.0	8.5	30.6	6.5	16	14.2	681	36
LT235/85R16	E	120/116 R	204-899	_____	6.5	6.0 - 7.5	9.3	32.0	7.1	17	14.8	652	42
LT225/75R16	E	115/112 R	204-287	_____	6.0	6.0 - 7.0	8.8	29.5	6.8	16	13.8	706	36
LT245/75R16	E	120/116 R	204-117	_____	7.0	6.5 - 8.0	9.8	30.7	7.4	16	14.3	679	40
LT245/70R17	E	119/116 R	204-304	_____	7.0	6.5 - 8.0	9.8	30.8	7.9	17	13.6	717	42