

TIMBERLINE HT COMMERCIAL



Outline	White Letter	LR	LI/SR	Article #	FET	Design Rim Width	Optional Rim Width	Section Width	Overall Dia.	Tread Width	Tread Depth (32nds)	Static Loaded Radius	Revs Per Mile	Wt.
LT265/75R16	E	123 /120 R	210-560	_____	7.5	7.0 - 8.0	10.5	31.7	8.0	15	14.7	659	44	
LT265/70R17	E	121 /118 R	205-698	_____	8.0	7.0 - 8.5	10.7	31.7	8.6	14	14.1	657	46	
Black														
LT215/85R16	E	115 /112 R	207-177	_____	6.0	5.5 - 7.0	8.5	30.4	6.5	14	14.1	686	38	
LT235/85R16	E	120 /116 R	205-664	_____	6.5	6.0 - 7.5	9.3	31.7	7.1	14	14.7	657	40	
LT225/75R16	E	115 /112 R	207-194	_____	6.0	6.0 - 7.0	8.8	29.3	6.8	14	13.6	712	36	
LT245/75R16	E	120 /116 R	205-647	_____	6.5	6.5 - 7.5	9.8	30.5	7.4	14	14.1	684	38	
LT245/70R17	E	119 /116 R	204-474	_____	7.0	6.5 - 8.0	9.8	30.6	7.4	14	14.3	683	41	

WIDETRACK BAJA A/S														
7.50-16LT	D		294-373	_____	6.0	5.5 - 7.0	9.0	31.8	6.5	13	14.7	655	42	
8.00R16.5LT	D	105/101 P	296-597	_____	6.0	6.0 - 6.75	8.0	28.3	5.8	13	13.3	736	30	

