



ROVER M/T MAXX TRACTION

Rugged Style Meets Bold Performance, On- And Off-Road



FEATURES	BENEFITS
Integrated Tread Pattern	On- and Off- Road Components help deliver excellent performance on multiple surfaces
Center On-Road Lugs	Help provide a quiet ride on pavement and good dry and wet handling
Multi-Pitch Tread Design Technology	Helps reduce noise for a quiet ride
Center Traction Lugs	Help provide excellent start-up and braking traction in sand, dirt, wet and winter conditions
Outer Self-Cleaning Channels	Help expel mud and debris for enhanced traction
Interlocking Center Line and Zig-Zag Sipes	Help provide forward and lateral bite in off-road conditions
Rim Flange Protector	Helps protect rims from accidental damage
Rugged Sidewall Styling	Sidewall edge elements create an aggressive, off-road appearance

Tire Size	Service Descrip.	Sidewall	Approved Rim Width	Measured Rim Width	Section Width	Outside Diameter	Tread Depth	Max. Load
37X13.50R20LT	<u>127Q</u>	BSL	8.5 - 11.0	11.00	13.6	36.5	18/32	3,860 @ 65
LT245/75R16	<u>120Q</u>	BSL	6.5 - 8.0	7.00	9.8	30.5	18/32	3,042 @ 80
LT265/70R17	<u>121Q</u>	BSL	7.0 - 8.5	8.00	10.7	31.7	18/32	3,195 @ 80
LT275/65R20	<u>126Q</u>	BSL	7.5 - 9.5	8.00	11.0	34.1	18/32	3,750 @ 80
LT275/70R18	<u>125Q</u>	BSL	7.0 - 8.5	8.00	11.0	33.2	18/32	3,640 @ 80
LT305/55R20	<u>121Q</u>	BSL	8.5 - 11.0	9.50	12.4	33.2	18/32	3,195 @ 65
LT315/70R17	<u>121Q</u>	BSL	8.5 - 10.0	9.50	12.7	34.4	18/32	3,195 @ 50
LT315/75R16	<u>127Q</u>	BSL	8.0 - 10.0	8.50	12.3	34.6	18/32	3,860 @ 65
37X13.50R18LT	<u>124Q</u>	BSL	8.5 - 11.0	11.00	13.6	36.5	18/32	3,525 @ 50
37X13.50R22LT	<u>123Q</u>	BSL	8.5 - 11.0	11.00	13.6	36.5	18/32	3,415 @ 65
LT265/75R16	<u>123Q</u>	OWL	7.0 - 8.0	7.50	10.5	31.7	18/32	3,415 @ 80
LT275/65R18	<u>123Q</u>	BSL	7.5 - 9.0	8.00	11.0	32.1	18/32	3,415 @ 80
LT285/70R17	<u>121Q</u>	OWL	7.5 - 9.0	8.50	11.5	32.8	18/32	3,195 @ 65
LT285/75R16	<u>126P</u>	OWL	7.5 - 9.0	8.00	11.3	32.8	18/32	3,750 @ 80
LT305/70R16	<u>124Q</u>	BSL	8.0 - 9.5	9.00	12.2	32.8	18/32	3,525 @ 65
LT325/60R20	<u>126Q</u>	BSL	9.0 - 12.0	9.50	13.0	35.4	18/32	3,750 @ 65
LT325/65R18	<u>127Q</u>	BSL	9.0 - 12.0	9.50	13.0	34.6	18/32	3,860 @ 65