



Wrangler MT/R

A Rugged Off-Road Tire Featuring Durawall™ Technology For Enhanced Sidewall Strength



Dry Traction	Wet Traction	Snow Traction	Off Road Traction	Quiet Ride
7	6	8	10	4

Features

Benefits

- | | |
|--|--|
| <ul style="list-style-type: none"> ◦ Durawall™ Technology ◦ Three-ply sidewall construction ◦ Wraparound tread ◦ High-tensile steel belts ◦ Staggered shoulder blocks | <ul style="list-style-type: none"> ◦ Helps resist cuts and tears in the sidewall area ◦ Helps provide toughness ◦ Offers superb off-road traction and toughness ◦ Help deliver on-road handling and off-road puncture resistance ◦ Offer aggressive off-road traction |
|--|--|

Tire Dimension Data & Other Technical Information

Tire Size	Product Code	Material Number	Load Range	Service Desc	Side wall	Tread Depth (32nds)	Approved Rim Width (min)	Approved Rim Width (max)	Measure Rim Width
LT235/75R15	750826020	00131506	C	104Q	OWL	18	6.0	7.0	6.50
30X9.50R15LT	750218020	00131495	C	104Q	OWL	19	6.5	8.5	7.50
31X10.50R15LT	750219020	00131499	C	109Q	OWL	19	7.0	9.0	8.50
32X11.50R15LT	750481020	00131502	C	113Q	OWL	20	8.0	10.0	9.00
33X12.50R15LT	750223020	00131488	C	108Q	OWL	20	8.5	11.0	10.00
35X12.50R15LT	750234020	00131492	C	113Q	OWL	20	8.5	11.0	10.00
35X12.50R15LT	750234092	00184099	C	113P	BSL	20	8.5	11.0	10.00
37X12.50R15LT	750230092	00164297	C	118P	BSL	20	0.0	8.5	1,011.00
LT255/70R16	750158020	00174148	C	108P	OWL	19	6.5	8.0	7.50
LT305/70R16	750394196	00182228	D	118P	OWL	20	8.0	9.5	9.00
LT245/75R16	750046092	00181913	E	120P	BSL	19	6.5	8.0	7.00
LT245/75R16	750831020	00131512	E	120P	OWL	19	6.5	8.0	7.00
LT265/75R16	750868196	00182226	D	119P	OWL	18	7.0	8.0	7.50
LT285/75R16	750906196	00182227	D	122P	OWL	19	7.5	9.0	8.00
LT315/75R16	750933196	00182225	D	121P	OWL	20	8.0	10.0	8.50
LT235/85R16	750825020	00131509	E	120P	OWL	19	6.0	7.0	6.50
225/75R16C	750476092	00197533	E	116N	BSL	18	6.0	7.0	6.00
LT245/70R17	750662020	00200357	E	119P	OWL	19	6.5	8.0	7.00
LT265/70R17	750668020	00200377	E	121P	OWL	19	7.0	8.5	8.00
LT275/70R17	750160020	00174150	C	114P	OWL	19	7.0	8.5	8.00
LT285/70R17	750148020	00175055	D	121P	OWL	19	7.5	9.0	8.50
LT305/70R17	750162020	00174810	D	119P	OWL	20	8.0	9.5	9.00
LT245/75R17	750663020	00200358	E	121P	OWL	19	6.5	7.5	7.00
37X12.50R17LT	750206092	00169260	E	129P	BSL	20	8.5	11.0	10.00
40X13.50R17LT	750292092	00185261	C	121P	BSL	20	8.5	11.0	11.00
LT275/65R18	750664020	00200359	E	123P	OWL	19	7.5	9.0	8.00

Tire Dimension Data & Other Technical Information (continued)

Tire Size	Product Code	Material Number	RPM	Maximum_Load @Maximum_PSI Single	Section Width	Overall Diameter	Weight (lbs)
LT235/75R15	750826020	00131506	718	1,985@50	9.3	29.1	37.2
30X9.50R15LT	750218020	00131495	702	1,985@50	9.5	29.8	40.7
31X10.50R15LT	750219020	00131499	679	2,270@50	10.5	30.8	46.1
32X11.50R15LT	750481020	00131502	658	2,535@50	11.4	31.5	49.5
33X12.50R15LT	750223020	00131488	638	2,205@35	12.5	32.8	56.6
35X12.50R15LT	750234020	00131492	601	2,535@35	12.5	34.8	60.8
35X12.50R15LT	750234092	00184099	601	2,535@35	12.5	34.8	64.2
37X12.50R15LT	750230092	00164297	569	2,270@35	12.5	36.5	63.4
LT255/70R16	750158020	00174148	690	2,205@50	10.2	30.3	45.0
LT305/70R16	750394196	00182228	633	2,910@50	12.2	32.8	59.4
LT245/75R16	750046092	00181913	681	3,042@80	9.8	30.7	47.9
LT245/75R16	750831020	00131512	681	3,042@80	9.8	30.7	47.6
LT265/75R16	750868196	00182226	656	3,000@65	10.5	31.6	51.9
LT285/75R16	750906196	00182227	632	3,305@65	11.3	33.1	56.5
LT315/75R16	750933196	00182225	601	3,195@50	12.3	34.6	65.1
LT235/85R16	750825020	00131509	654	3,042@80	9.3	32.0	47.6
225/75R16C	750476092	00197533	709	2,756@70	8.8	29.3	41.8
LT245/70R17	750662020	00200357	680	3,000@80	9.8	30.5	47.1
LT265/70R17	750668020	00200377	656	3,195@80	10.7	31.6	51.2
LT275/70R17	750160020	00174150	644	2,600@50	11.0	32.4	49.3
LT285/70R17	750148020	00175055	634	3,195@65	11.5	33.0	55.0
LT305/70R17	750162020	00174810	613	3,000@50	12.2	34.1	64.4
LT245/75R17	750663020	00200358	659	3,195@80	9.8	31.5	49.5
37X12.50R17LT	750206092	00169260	569	4,080@65	12.5	36.8	80.2
40X13.50R17LT	750292092	00185261	575	3,195@35	13.5	39.8	92.1
LT275/65R18	750664020	00200359	647	3,415@80	11.0	32.1	53.8