

# FIERCE UHP

## ULTRA HIGH-PERFORMANCE INTENSITY THAT STANDS OUT

Get an intense directional look that will not only help your car stand out, but it will help enhance traction and handling for one sick ride.

### FEATURES & BENEFITS

Low profile, wider footprint and Z-speed rating provide ultra high-performance appearance and enhanced handling

Directional tread design and natural-flow tread grooves help sweep away water

Shoulder tread elements enhance cornering and traction

Refined bead area promotes uniform and balanced ride

Rim protector to help guard rims against accidental curb damage

High-performance tread compound helps provide enhanced wet and dry traction



## SPECIFICATIONS

SIZE	SERVICE DESCRIPTION	LOAD RANGE	SIDEWALL	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	TREAD DEPTH (IN 32NDS)	REVS PER MILE	MAX LOAD (LBS)	MAX INFL. (PSI)
205/50ZR16	87W	SL	SBL	353542147	200052	5.5 - 7.5	6.5	8.1	24.1	10	867	1,201	44
225/50ZR16	92W	SL	SBL	353097147	200059	6.0 - 8.0	7.0	8.9	24.9	10	839	1,389	44
245/50ZR16	97W	SL	SBL	353548147	200065	7.0 - 8.5	7.5	9.6	25.7	10	815	1,609	44
205/55ZR16	91W	SL	SBL	353374147	200054	5.5 - 7.5	6.5	8.1	24.9	10	839	1,356	44
225/55ZR16	95W	SL	SBL	353414147	200060	6.0 - 8.0	7.0	8.9	25.8	10	812	1,521	44
245/40ZR17	91W	SL	SBL	353545147	200063	8.0 - 9.5	8.5	9.6	24.7	10	846	1,356	44
255/40ZR17	94W	SL	SBL	353549147	200067	8.5 - 10.0	9.0	10.0	25.1	10	834	1,477	44
275/40ZR17	98W	SL	SBL	353551147	200069	9.0 - 11.0	9.5	10.8	25.7	10	815	1,653	44
215/45ZR17	87W	SL	SBL	353378147	200056	7.0 - 8.0	7.0	8.5	24.7	10	848	1,201	44
225/45ZR17	91W	SL	SBL	353380147	200058	7.0 - 8.5	7.5	8.9	25.0	10	838	1,356	44
235/45ZR17	94W	SL	SBL	353544147	200062	7.5 - 9.0	8.0	9.3	25.4	10	824	1,477	44
245/45ZR17	95W	SL	SBL	353547147	200064	7.5 - 9.0	8.0	9.6	25.7	10	815	1,521	44
265/35ZR18	93W	SL	SBL	353550147	200068	9.0 - 10.5	9.5	10.4	25.3	10	826	1,433	44
225/40ZR18	88W	SL	SBL	353379147	200057	7.5 - 9.0	8.0	8.9	25.1	10	833	1,235	44
235/40ZR18	91W	SL	SBL	353543147	200061	8.0 - 9.5	8.5	9.3	25.4	10	823	1,356	44