



# Safari® TSR

Rugged, All-Terrain Traction Tire With Enhanced Grip Both On- And Off-Highway

- 1 Patented rock patterned tread
- 2 Deep, self-cleaning tread elements and staggered shoulder blocks
- 3 Pinned for #16 metal studs \*
- 4 Rim protector
- 5 Multi-directional zigzag siping
- 6 Non-symmetric, free-form interlocking tread blocks



\* Consult state laws regarding stud use. Use stud #16

† See 30-Day Test Drive Brochure for complete details

## ▼ Kelly Tires Features Sizes And Specs

TIRE SIZE	SERVICE DESCR.	LOAD RANGE	SIDE-WALL DESCR.	APPROVED RIM WIDTH (INS)	MEAS. RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	TREAD DEPTH (IN 32NDS)	MAX LOAD (LBS)
31X10.50R15LT	100Q	C	OWL	7.0 - 9.0	8.50	10.5	30.5	16/32	2,270@50
LT235/75R15	100Q	C	OWL	6.0 - 7.0	6.50	235	28.9	16/32	1,985@50
LT235/85R16	100Q	E	BSL	6.0 - 7.5	6.50	235	31.7	16/32	3,042@80
LT245/75R16	100Q	E	BSL	6.5 - 8.0	7.00	245	30.5	18/32	3,042@80
LT245/75R17	100Q	E	OWL	6.5 - 7.5	7.00	245	31.5	18/32	3,195@80
LT265/70R17	100Q	E	BSL	7.0 - 8.5	8.00	265	31.7	18/32	3,195@80
LT265/75R16	100Q	E	OWL	7.0 - 8.0	7.50	265	31.7	18/32	3,415@80
LT275/65R18	100Q	E	BSL	7.5 - 9.0	8.00	275	32.1	18/32	3,415@80
LT285/70R17	100Q	D	OWL	7.5 - 9.0	8.50	285	32.8	18/32	3,195@65
LT285/75R16	94P	E	OWL	7.5 - 9.0	8.00	285	32.8	18/32	3,750@80
LT315/70R17	100Q	D	BSL	8.5 - 10.0	9.50	315	34.4	18/32	3,195@50
LT315/75R16	100Q	E	BSL	8.0 - 10.0	8.50	315	34.6	18/32	3,860@65