



# Safari Trex® Featuring VersaTred®

Premium All-Terrain Tire For Quiet,  
Even-Wearing Truck Comfort

- 1 Elongated rib and multi-pitch tread design
- 2 Unique tread pattern and element geometry
- 3 Below-surface geometry
- 4 Enhanced cavity shape
- 5 Advanced bead-area design
- 6 Tread Life Limited Warranty\* (P-Metric sizes only)



\* See Tread Life Limited Warranty Brochure for complete details

† See 30-Day Test Drive Brochure for complete details



## ▼ Kelly Tires Features Sizes And Specs

TIRE SIZE	SERVICE DESCR.	LOAD RANGE	SIDE-WALL DESCR.	APPROVED RIM WIDTH (INS)	MEAS. RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	TREAD DEPTH (IN 32NDS)	MAX LOAD (LBS)
31X10.50R15LT	94P	C	OWL	7.0 - 9.0	8.50	10.5	30.5	18/32	2,270@50
LT215/85R16	94P	E	SBL	5.5 - 7.0	6.00	215	30.4	16/32	2,680@80
LT225/75R16	100Q	E	BSL	6.0 - 7.0	6.50	225	29.3	16/32	2,680@80
LT235/75R15	94P	C	OWL	6.0 - 7.0	6.50	235	28.8	16/32	1,985@50
LT235/85R16	100Q	E	SBL	6.0 - 7.0	6.50	235	31.8	16/32	3,042@80
LT245/70R17	100Q	E	OWL	6.5 - 8.0	7.00	245	30.5	16/32	3,000@80
LT245/75R16	100Q	E	OWL	6.5 - 7.5	7.00	245	30.5	16/32	3,042@80
LT245/75R17	100Q	E	OWL	6.5 - 7.5	7.00	245	31.5	16/32	3,195@80
LT265/70R17	100Q	E	OWL	7.0 - 8.5	8.00	265	31.7	16/32	3,195@80
LT265/75R16	100Q	E	OWL	7.0 - 8.0	7.50	265	31.6	16/32	3,415@80
LT285/70R17	100Q	D	OWL	7.5 - 9.0	8.50	285	32.8	14/32	3,195@65
LT285/75R16	100Q	E	OWL	7.5 - 9.0	8.00	285	32.9	16/32	3,750@80
P205/75R15	112S	SL	OWL	5.0 - 7.0	5.50	205	27.1	11/32	1,453@44
P215/75R15	112S	SL	OWL	5.5 - 7.0	6.00	215	27.7	11/32	1,584@44
P225/75R15	112S	SL	OWL	6.0 - 7.5	6.00	225	28.3	11/32	1,704@44
P225/75R16	112S	SL	OWL	6.0 - 7.5	6.00	225	29.3	11/32	1,804@44
P235/65R17	112S	SL	OWL	6.5 - 8.5	7.00	235	29.0	14/32	1,754@44
P235/70R16	112S	SL	OWL	6.0 - 8.0	7.00	235	29.0	12/32	1,804@44
P235/75R15	112S	SL	OWL	6.0 - 8.0	6.50	235	28.8	12/32	1,844@44
P235/75R16	112S	SL	OWL	6.0 - 8.0	6.50	235	29.8	12/32	1,904@44
P245/65R17	112S	SL	OWL	7.0 - 8.5	7.00	245	29.5	11/32	2,039@51
P245/70R16	112S	SL	OWL	8.0 - 6.5	7.00	245	29.5	13/32	1,904@44
P245/70R17	112S	SL	OWL	6.5 - 8.0	7.00	245	30.5	13/32	2,005@44
P245/75R16	112S	SL	OWL	6.5 - 8.0	7.00	245	30.5	12/32	2,065@44
P255/65R17	112S	SL	OWL	7.0 - 9.0	7.50	255	30.1	12/32	2,004@44
P255/70R16	112S	SL	OWL	6.5 - 8.5	7.50	255	30.1	13/32	2,065@44
P265/65R17	112S	SL	OWL	7.5 - 9.5	8.00	265	30.5	12/32	2,124@44
P265/70R15	112S	SL	OWL	7.0 - 9.0	8.00	265	29.6	12/32	2,125@44
P265/70R16	112S	SL	OWL	7.0 - 9.0	8.00	265	30.6	13/32	2,185@44
P265/70R17	112S	SL	OWL	7.0 - 9.0	8.00	265	31.6	14/32	2,305@44
P265/70R18	112S	SL	BSW	7.0 - 9.0	8.00	265	32.6	11/32	2,601@51
P265/75R16	112S	SL	OWL	7.0 - 9.0	7.50	265	31.6	12/32	2,365@44