



Eagle F1 GS D3

Commanding Wet Traction For Ultra High-Performance Driving

UTQG:
Treadwear: 280
Traction: AA
Temperature: A



Dry Traction	Wet Traction	Snow Traction	Ride Comfort	Quiet Ride
9	10	N.R.	8	8
Features			Benefits	
<ul style="list-style-type: none"> ◦ Directional OneTRED™ design with three integrated tread zones ◦ V-TRED™ Technology ◦ AAttrax tread compound provides "AA" wet traction rating ◦ Rim protector 			<ul style="list-style-type: none"> ◦ Superior traction and handling with sleek Euro-inspired appearance ◦ Excellent wet traction and smooth, quiet ride ◦ Outstanding wet and dry grip without sacrificing treadwear ◦ Helps protect wheels against accidental curb damage 	

Tire Dimension Data & Other Technical Information

Tire Size	Product Code	Material Number	Service Desc	Side wall	App Rim Width (min)	App Rim Width (max)	Meas Rim Width	Overall Width	Overall Diameter	Max Load	RPM	Tread Depth (32nds)	Weight (lbs)
225/502R16	70930515400184564		92Y	BLT	6.0	8.0	7.00	9.2	24.9	1,389	840	11	23.9
245/502R16	70925515400184091		97Y	VS8	7.0	8.5	7.50	10.0	25.7	1,609	814	10	27.7
205/552R16	70929415400184483		91W	VS8	5.5	7.5	6.50	8.4	24.9	1,356	840	11	21.2
225/552R16	70926215400184104		95Y	VS8	6.0	8.0	7.00	9.2	25.8	1,521	812	10	26.2
315/352R17	70926015400184094		102Y	VS8	10.5	12.5	11.00	12.6	25.7	1,874	814	10	31.1
245/402R17	70931415400184567		91Y	VS8	8.0	9.5	8.50	9.8	24.7	1,356	845	11	23.5
255/402R17	70927415400184570		94Y	VS8	8.5	10.0	9.00	10.2	25.0	1,477	835	11	25.2
275/402R17	70925415400184090		98Y	VS8	9.0	11.0	9.50	10.9	25.7	1,653	814	10	28.1
285/402R17	70925715400184093		100Y	VS8	9.5	11.0	10.00	11.4	26.0	1,764	804	10	29.4
215/452R17	70936015400184783		91Y	VS8	7.0	8.0	7.00	8.4	24.7	1,356	848	10	22.3
225/452R17	70930715400184565		91Y	VS8	7.0	8.5	7.50	8.9	25.0	1,356	837	11	23.6
225/452R17	70972115400188662		94W	VS8	7.0	8.5	7.50	8.9	25.0	1,477	837	11	24.4
245/452R17	70915615400184085		95Y	VS8	7.5	9.0	8.00	9.6	25.7	1,521	814	10	26.8
255/452R17	70925615400184092		98Y	VS8	8.0	9.5	8.50	10.0	26.1	1,653	802	10	26.4
225/502R17	70972215400188663		94Y	VS8	6.0	8.0	7.00	9.2	25.9	1,477	807	11	23.9
225/552R17	70972615400188665		101W	VS8	6.0	8.0	7.00	9.2	26.8	1,819	781	11	25.9
245/352R18	70971515400184499		88Y	VS8	8.0	9.5	8.50	9.8	24.8	1,235	844	11	24.0
285/352R18	70973715400188678		97Y	VS8	9.5	11.0	10.00	11.4	25.9	1,609	808	11	29.0
295/352R18	70974315400195284		99Y	VS8	10.0	11.5	10.50	11.9	26.1	1,709	801	10	30.0
225/402R18	70941115400184494		92Y	VS8	7.5	9.0	8.00	9.1	25.1	1,389	833	11	23.4
235/402R18	70927115400184496		91Y	VS8	8.0	9.5	8.50	9.5	25.4	1,356	823	11	25.1
255/402R18	70973215400188673		95Y	VS8	8.5	10.0	9.00	10.2	26.0	1,521	803	11	27.0
275/402R18	70925315400184089		99Y	VS8	9.0	11.0	9.50	10.9	26.7	1,709	784	10	28.0
245/452R18	70956315400197873		100W	VS8	7.5	9.0	8.00	9.6	26.7	1,764	784	10	28.2
255/452R18	70936315400184784		103Y	VS8	8.0	9.5	8.50	10.0	27.1	1,929	773	11	31.0
235/50R18	70900128100207568		97V	BLT	6.5	8.5	7.50	9.6	27.3	1,609	766	11	24.0
235/502R18	70930315400184501		101Y	VS8	6.5	8.5	7.50	9.7	27.3	1,819	766	11	28.4

245/502R1870974515400195286	100W	VSB	7.0	8.5	7.50	10.0	27.7	1,764	755	10	30.4
255/552R1870961315400202040	109Y	VSB	7.0	9.0	8.00	10.4	29.0	2,271	720	10	31.6
265/302R1970973315400188674	93Y	VSB	9.0	10.0	9.50	10.7	25.3	1,433	826	11	26.0
245/352R1970938715400184516	93Y	VSB	8.0	9.5	8.50	9.8	25.8	1,433	810	11	27.0
255/352R1970973015400188672	96Y	VSB	8.5	10.0	9.00	10.2	26.0	1,565	803	11	26.0
245/402R1970934015400184508	98Y	VSB	8.0	9.5	8.50	9.8	26.7	1,653	782	10	26.9
245/402R1970955115400205191	(94Y)	BLT	8.0	9.5	8.50	9.8	26.7	1,477	782	9	26.2
255/402R1970935615400184573	96Y	VSB	8.5	10.0	9.00	10.2	27.1	1,566	773	11	29.0
275/402R1970973815400195282	101Y	VSB	9.0	11.0	9.50	10.9	27.7	1,819	755	10	31.4
245/452R1970973915400195283	98Y	VSB	7.5	9.0	8.00	9.6	27.7	1,653	755	10	29.0
265/502R1970969615400203925	110Y	VSB	7.5	9.5	8.50	10.9	29.5	2,337	709	10	33.5
305/352R2070984715400205192	(104Y)	VSB	10.0	12.0	11.00	12.3	28.4	1,984	735	10	32.8
275/452R2070960815400201632	110Y	VSB	8.5	10.5	9.00	10.7	29.8	2,337	702	10	35.1
245/352R2170935015400184510	96Y	VSB	8.0	9.5	8.50	9.8	27.8	1,566	753	11	27.3