



Snowtraker® Radial ST/2

Winter Tire Offering Traction In Ice, Snow And Rain

- 1 High-density blading
- 2 Two circumferential grooves
- 3 Wide, self-cleaning tread
- 4 Unique in/out shoulder lug design
- 5 M+S Rated
- 6 Pinned for #13 metal studs *



Mountain Snowflake
Symbol Designation For
Outstanding Winter Traction



* Consult state laws regarding use. Use stud #13.

▼ Kelly Tires Features Sizes And Specs

TIRE SIZE	SERVICE DESCR.	LOAD RANGE	SIDE-WALL DESCR.	APPROVED RIM WIDTH (INS)	MEAS. RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	TREAD DEPTH (IN 32NDS)	MAX LOAD (LBS)
175/70R14	112S	SL	SBL	4.5 - 6.0	5.00	175	23.7	13/32	1,102@44
185/60R15	112S	SL	SBL	5.0 - 6.5	5.50	185	24.0	13/32	1,102@44
195/55R15	112S	SL	SBL	5.5 - 7.0	6.00	195	23.7	13/32	1,135@44
205/60R16	112S	SL	SBL	5.5 - 7.5	6.00	205	25.9	13/32	1,389@44
215/60R15	112S	SL	SBL	6.0 - 7.5	6.50	215	25.4	13/32	1,477@44
215/65R15	112S	SL	SBL	6.0 - 7.5	6.50	215	26.3	13/32	1,565@44
215/65R16	112S	SL	SBL	6.0 - 7.5	6.50	215	27.2	13/32	1,653@44
225/75R15	112S	SL	SBL	6.0 - 7.5	6.00	225	28.3	15/32	1,874@44
P175/65R14	112S	SL	SBL	5.0 - 6.0	5.00	175	23.2	12/32	1,019@44
P185/60R14	112S	SL	SBL	5.0 - 6.5	5.50	185	23.0	13/32	1,047@44
P185/65R14	112S	SL	SBL	5.0 - 6.5	5.50	185	23.6	13/32	1,124@44
P185/65R15	112S	SL	SBL	5.0 - 6.5	5.50	185	24.6	13/32	1,168@44
P185/70R14	112S	SL	SBL	4.5 - 6.0	5.50	185	24.5	13/32	1,201@44
P185/75R14		SL	SBL	4.5 - 6.0	5.00	185	25.0	0/32	1,290@35
P195/60R15	112S	SL	SBL	5.5 - 7.0	6.00	195	24.4	13/32	1,190@44
P195/65R15	112S	SL	SBL	5.5 - 7.0	6.00	195	25.2	13/32	1,279@44
P195/70R14	112S	SL	SBL	5.0 - 6.5	6.00	195	25.0	13/32	1,323@44
P195/75R14		SL	SBL	5.0 - 6.5	5.50	195	25.5	0/32	1,400@35
P205/55R16	112S	SL	SBL	5.5 - 7.5	6.50	205	25.1	13/32	1,279@44
P205/60R15	112S	SL	SBL	5.5 - 7.5	6.00	205	24.9	13/32	1,323@44
P205/65R15	112S	SL	SBL	5.5 - 7.5	6.00	205	25.6	13/32	1,400@44
P205/70R15	112S	SL	SBL	5.0 - 7.0	6.00	205	25.4	0/32	1,499@44
P205/75R14		SL	SBL	5.0 - 7.0	5.50	205	26.1	0/32	1,400@35
P205/75R15		SL	SBL	5.0 - 7.0	5.50	205	27.1	0/32	1,598@35
P215/60R16	112S	SL	SBL	6.0 - 7.5	6.50	215	26.3	13/32	1,477@44
P215/70R15	112S	SL	SBL	5.5 - 7.0	6.50	215	26.9	0/32	1,620@44
P215/75R15		SL	SBL	5.5 - 7.0	6.00	215	27.7	0/32	1,742@35
P225/60R16	112S	SL	SBL	6.0 - 8.0	6.50	225	26.8	13/32	1,609@44
P235/75R15		XL	SBL	6.0 - 8.0	6.50	235	28.9	14/32	2,183@41